



BS 2903

Global BS 2903 **ELECTRONIC DIRECT DRIVE LOCKSTITCH BUTTON SEWER**

Computer controlled high-speed lockstitch button attaching sewing machine. This machine is driven by a Ho Hsing direct drive AC servomotor for sewing medium size buttons. Equipped with automatic thread trimmer. Standard delivered with 33 stitch patterns.

Máquina electrónica de pespunte para poner botones, accionada por Ho Hsing motores AC servo directo, adecuada para coser botones medio. Equipada con corta-hilos automático. Equipada standard con 33 patrones fijos.

Diese Maschine wird angetrieben durch einem integriertem Ho Hsing Servomotor und ist geeignet für annähen von Knöpfe mit mittlerem Knopfgröße. Standard geliefert mit (fest eingegebenen) 33 Stichbildern. Ausgestattet mit automatischer Fadenabschneider.

Machine pose boutons, point noué à commande par Ho Hsing servomoteur AC et compatible pour la couture de boutons de taille moyenne. En standard 33 programmes. Equipée avec coupe-fils automatique.

TECHNICAL SPECIFICATIONS

MACHINE SPEED
max 2500 spm

FEEDING SYSTEM
By pulse motor (X- Y)

HOOK TYPE
Standard shuttle hook

NEEDLE TYPE
DP x 17

BUTTON SIZE
Ø 8 – Ø 20 mm

SEWING SIZE
X : 0,1 – 6,5 mm
Y : 0,1 – 6,5 mm

INDUSTRIAL SEWING MACHINES