

- SEMI DRY MACHINE HEAD
- BUILT IN HO HSING SERVO-MOTOR
- LOW NOISE
- LITTLE VIBRATION
- LOW OIL CONSUMPTION
- LIGHT/HEAVY FABRICS
- LARGER WORK SPACE
- GREAT STOP ACCURACY



3200 H-AUT

Global 3200 AUT Series

HIGH SPEED, SEMI DRY LOCKSTITCH MACHINES

3200 AUT

Semi dry head, single needle lockstitch machine driven by built-in Ho Hsing mini servo motor. Machine is equipped with a thread trimming device, automatic back tack, presser foot lift and wiper (all electric).

Máquina de pespunte en seco de una aguja con el motor servo incorporado. La máquina esta equipada con corta-hilos, remate eléctrico y alza-prensatelas.

Einnadel, Hochgeschwindigkeits Schnellnäher mit eingebautem mini Servomotor. Maschine ist standard mit elektrischer Fadenabschneider, automatischer Verriegelung und Presserfußlüftung ausgestattet.

Machine tête semi sèche, une aiguille point noué avec mini moteur servo intégré. La machine est équipée d'un dispositif coupe fil, point d'arrêt automatiques et relevage du pied presseur (électro-aimant).

3200 H-AUT

Same as above, but equipped for medium to heavy work.

Las mismas características que la anterior, pero equipada para materiales medios y pesados.

Baugleich mit 3200 AUT, jedoch geeignet für mittleres bis schweres Material.

Identique au modèle 3200 AUT, mais recommandée pour les matériaux moyens à lourds.

TECHNICAL SPECIFICATIONS

MACHINE SPEED

3200 AUT - max 5000 spm
3200 H-AUT - max 4500 spm

OILING SYSTEM

semi dry head

STITCH LENGTH

max 5 mm

PRESSER FOOT LIFT

max 7 mm (electric)

NEEDLE BAR STROKE

3200 AUT - 31 mm
3200 H-AUT - 35 mm

NEEDLE TYPE

134R

POWER SOURCE

240V single phase
50/60 Hz
Ho Hsing direct drive
mini servo motor