

- semi dry machine head
- built in servomotor
- low noise
- little vibration
- low oil consumption
- light/medium fabrics
- larger work space
- great stop accuracy



390 AUT



Advanced oiling system

Global[®] 390 Series - High speed, semi dry lockstitch machines

TECHNICAL SPECIFICATIONS

Machine speed*
up to 5000 spm
Stitch length
4 mm
Presser foot lift
by hand 5 mm
by knee 14 mm
Needle type
134 R
Needle bar stroke
30 mm
Number of needles
1
Dimensions of bedplate
517x178 mm
Power source
240V 1Ph - 50/60 Hz
direct drive
mini servo motor
made by Ho Hsing
Electric presser foot lift
optional

390 AUT - Semi dry head, single needle lockstitch machine driven by built in mini servo motor. Machine is equipped with a thread trimming device and auto back tack (solenoid).

MÁQUINA DE PESPUNTE DE ALTA VELOCIDAD FUNCIONANDO EN SECO

390 AUT - Máquina de pespunte en seco de una aguja con el motor servo incorporado. La máquina esta equipada con corta-hilos y remate eléctrico.

FAST ÖLFREIE DOPPELSTEEPSTICH MASCHINE

390 AUT - Einnadel, Hochgeschwindigkeits Schnellnäher mit eingebautem mini Servomotor. Maschine ist mit magn. Fadenabschneider und automatischer Verriegelung.

MACHINE POINT NOUÉ, TÊTE SEMI-SÈCHE, TRÈS GRANDE VITESSE

390 AUT - Machine tête semi sèche, une aiguille point noué avec mini moteur servo intégré. La machine est équipée d'un dispositif coupe fil et des arrêts automatiques (électro-aimant).

★ Max. sewing speed (in spm.) depends on type of operation and/or materials to be sewn.

The GLOBAL[®] Selection is brought to you by:

GLOBAL[®] is a trademark of the Global International Corporation, the people that carefully organize the supply of spareparts before they launch each product.

When ordering parts please specify:

- 1 machine model
- 2 part numbers