



EM 119-2N-P MK



EM 119-2N-P MK

## Global EM 119-2N Series

### PICOT SEWING MACHINES

#### EM 119-2N

Picot sewing machine. The machine is equipped with two needles and two rotating hooks with a puncher in between. The needle threads overedge the sides of the hole made in the fabric by the puncher. Suitable for shirts, ties, handkerchiefs, towels etc.

Máquina de puntilla. La máquina está equipada con dos agujas y dos garfios giratorios con un perforador en medio. La aguja hebra sobre el filo de los lados del agujero hecho en la fábrica con el perforador. Adecuada para camisetos, corbatas, pañuelos, toallas, etc.

Kettenstich Zierstichmaschine. Diese Maschine verfügt über 2 Nadeln und 2 Rotierenden Greifern und ein Stanzeisen in der Mittel. Zum nähen von Hemdbluse, Taschentuch, Krawatte, Tischtuch u.s.w.  
Machines pour point jour venise. La machine est équipée avec 2 aiguilles et 2 crochets avec un perforateur au milieu. Les fils d'aiguilles bourdonnent les côtés des perforations faites par le poinçon dans le tissu. Recommandée pour chemises, mouchoirs, linge de maison, etc.

#### EM 119-2N-P MK

Same as EM 119-2 N, but equipped with puller and middle knife.

Las mismas características que la EM 119-2 N, pero con puller y cuchillo medio.

Baugleich mit EM 119-2 N, jedoch mit puller und mittel Messer.

Identique à la version EM 119-2 N avec en plus, puller et couteau moyen.

### TECHNICAL SPECIFICATIONS

**MACHINE SPEED**  
max 2250 spm

**OILING SYSTEM**  
manual

**STITCH WIDTH**  
max 5 mm

**PRESSER FOOT LIFT**  
max 5 mm

**NEEDLE TYPE**

- DB x 1 stitch needle
- PKG x 8 front guiding needle
- PKZ x 1 rear base needle