



BM 9260-DD



BM 9280 DD



BM 9352-DD

6A - \$\$\$188.09F-9G

## Global BM 9000-DD Series VARIOUS BLINDSTITCH MACHINES

### BM 9260-DD

- High speed, single thread, blindstitch beltloop sewing machine. Fabric is cut to required width, then folded and sewn into 10 mm beltloops. No skip stitch mechanism. Driven by built-on mini servo motor & control box.
- Máquina de puntada invisible de una aguja y un hilo para coser pasadores de cintura. El tejido es cortado a la anchura requerida y los pasadores doblados y cosidos a 10 mm de anchura. Sin saltador de puntada.
- Einfaden Blindstich - Gürtelschlaufen-Maschine. Der Stoff wird in der gewünschte Breite geschnitten, gefaltet und zu 10 mm breiten Gürtelschlaufen genäht. Die Maschine hat keine Intervall-Einrichtung.
- Machine point invisible une aiguille, 1 fil à grande vitesse pour réalisation de passants. Les tissus est coupé à largeur requise, ensuite remplié et cousu en passants de largeur 10 mm. Pas de dispositif de point sauté.

### BM 9280-DD

- Single thread blindstitch machine, driven by built-on mini servo motor and control box for blind hemming of the waistband.
- Máquina de puntada invisible, con el mini motor de tracción directa y caja de control, un hilo para hilvanar el forro de la pretina del pantalón.
- Einfaden - Hosenbundfutter - Staffi ermaschine, ausgestattet mit Direct Drive Servo Motor und Steuerkasten.
- Machine point invisible un fil pour glaçage des ceintures, avec un moteur à commande Directe et boîte de contrôle.

### BM 9352-DD

- High speed blindstitch machine equipped with independant adjustable plungers for sewing over cross seams on light / medium materials. Driven by built-on mini servo motor and control box.
- Máquina de puntada invisible de alta velocidad com doble leva, ajustable independientemente, para coser en materiales con costuras trasversales. Para materiales ligeras y media pesadas.
- Hochgeschwindigkeits, Blindstichmaschine mit unabhängig von einander einstellbaren Taucher, geeignet für kreuzende Säume an leichtes bis mittleres Materialien.
- Machine point invisible rapide équipée avec des plongeurs indépendants pour le passage de couture transversal sur des matières léger à moyen.

### TECHNICAL SPECIFICATIONS

**MACHINE SPEED**  
max 2000 spm

**STITCH LENGTH**  
min. 3 mm  
max. 8 mm

**NEEDLE TYPE**  
BM 9260-DD / BM 9280-DD  
2140 TP / LW x 6T

BM 9352-DD  
251 EU

**SKIP STITCH**  
1:1 - 2:1

INDUSTRIAL SEWING MACHINES

## Global BM 9000-DD Series

VARIOUS BLINDSTITCH MACHINES FOR LIGHT TO MEDIUM MATERIALS



### Global® BM 9280-DD Blindstitch machine


With this high speed blindstitch machine the waistband linings are attached on european-style trousers (blindstitch seam lies on top of the waistband seam). Due to the spring-loaded presser foot, this machine overcomes the change of thickness free of marks (p.e. at cross seams, pocket bags).



### Global® BM 9260-DD Belt loop machine

The fabric is first cut to size by two knives, then passes through a folder and sewn by one thread blindstitch to produce a perfect 10 mm double belt loop, suited to classic men's and women's wear.

non skip  
1:1



### Global® BM 9352-DD Double plunger machine

For medium to heavy materials with two spring-loaded plungers. When sewing over cross seams, automatically spring down so that the needle pierces the upper cloth layer only. The two presser feet shoes act like a scanner and are adjustable to the thickness of the fabric.

## SPECIFICATIONS

MODEL	NUMBER OF NEEDLES	MAX. STITCH LENGTH MM	Materials L M	NEEDLE SYSTEM	NUMBER OF THREADS	PRESSER FOOT LIFT (MM)	HEMMING	BELT LOOP SYSTEM	MAX. SEWING SPEED
BM 9260-DD	1	8	- •	2140 TP	1	12	- •	• -	2000
BM 9280 DD	1	8	- •	2140 TP	1	12	• •	- -	2000
BM 9352-DD	1	8	- •	251 EU	1	12	• •	- -	2200